

Codan 3133 Petrol Hose



Codan 3133 - SAE J30 R9 and MGRES22RU49 Class 1A

Black, flexible hose for fuel in automotive or engine application. High resistance to all above media and especially used in Car, Truck, Agricultural and Construction equipment vehicles for fuel injection systems. High temp hose with low permeation for Petrol at less than 15g/m²/24hrs. Normally installed using crimped ferrules or petrol hose clips. Suitable for petrol, diesel, ethanol, gasoline, oxidized sour gas, oil, bio-diesel.

Intermittent Temperature: +150C

Please contact Codan for further information.

Type nr. 3133

Application: Petrol / Diesel / Bio-diesel

Standard Length: 50 metres

Working Temperature: -30°C to 130°C

Inside: FKM/NBR

Colour: Black

Reinforcement: PET

Outside: CPE

Colour: Black

Standards: SAE J30 R9 and MGRES22RU49 Class 1A

Inside dia. (mm)	Outside dia. (mm)	Working Pressure BAR	Burst Pressure BAR	Bend Radius (mm)	Weight (g/m)	Product code
4,8	11,8	10	62	46	195	3133048000
5,6	12,0	10	62	52	130	3133056000
6,3	12,7	10	62	56	150	3133006000
7,0	14,6	10	62	60	195	3133007000
7,1	13,2	10	62	60	195	3133071000
7,9	14,5	10	62	58	180	3133008000
9,5	16,5	10	62	62	230	3133095000
15,6	22,4	10	62	76	271	3133016000

This hose specification sheet has been prepared with great care in order to provide you with all the information you need. Written advice must be obtained from Codan Rubber before using any hose with untested media or before using in applications not covered in the product data sheet. Codan Rubber recommends regular maintenance, care and inspection of hoses before use. Hoses should be replaced if any physical damage is seen, especially to the cover of the hose or in the area around the couplings. All products must be stored in accordance with ISO 2230:2002 (Storage

of vulcanised Rubber Products). The individual conditions of an application will affect the life time of each product. Therefore please ensure that resistance to chemicals and cleaning procedures in our written product information is complied with. Codan Rubber's warranty is void in the event of misuse such as excessive bending, crushing, stretching, use with incorrect media or use in environments outside the hose specification.

Please contact Codan Rubber for individual product manufacturing tolerances.



© Codan Rubber Danmark A/S Valdemarshaab 1, DK-4600 Køge, Denmark
Tel. +45 56 64 64 64 Fax +45 56 64 65 48 Mail: info@codan.com www.codan.com

19/05/2015